



Stahlin Non-Metallic Enclosures
500 Maple Street
Belding, Michigan 48809
Phone: 616-794-0700
Fax: 616-794-3378
Email: Stahlin2@robroy.com

Stahlin Non-Metallic Enclosures New NW-Series Bonded Windows New Datasheet Available For Easy Download

03/09/2010

Stahlin Non-Metallic Enclosures New NW-Series Bonded Windows New Datasheet Available For Easy Download

Belding, MICHIGAN --- Stahlin Non-Metallic Enclosures, manufacturer of the world's most frequently specified fiberglass enclosure products, introduces the new NW-Series Bonded Window Enclosures. Stahlin's NW-Series of non-metallic bonded window enclosures provides you a range of 8 standard size offerings.

Plus ---- Stahlin offers the capability of creating any modified N-Series enclosure up to a 41 33 bonded window and certified by UL/cUL type 1, 3R, 4X, 12 ratings. Just call us for details.

Stahlin NW-Series Bonded Window Enclosures meet NEMA 250 Type: 1, 3R, 4X, and 12 standards ---- feature a temperature range from -76 degrees F to 266 degrees F) ---provide UL94-5V flammability rating plus the assurance of a NFPA No. 101: Flame Spread Class A (1).

Stahlin's NW-Series Bonded Window Enclosures Feature Patented SolarGuard® Stahlin NW-Series Bonded Window Enclosures are molded from the most unique compounding formula available --- SolarGuard® --- a patented, non-halogenated fiberglass system that outperforms other available SMC formulations by as much as 60% in its ability to retain gloss and color. SolarGuard® meets a NFPA No. 101 Class A flame spread index. Fire retardant; meets UL 94-5V standards.

Window Material: Super Abrasion Resistant (SAR) Acrylic In addition, windows featured in Stahlin NW-Series Bonded Window Enclosures are constructed from Super Abrasion Resistant (SAR) acrylic produced by applying a very hard, highly cross-linked polysilicate coating to a substrate. This coating provides a surface that has 45 times the abrasion resistance of uncoated acrylic.

The Physical Features of Stahlin's NW-Series Bonded Window Enclosures Include: • Enclosure size ranges from 20" X 16" to 48" X 36" • Flush mounted, lightweight, very durable acrylic window • Maximized viewable window sizes • Rigid body construction and watertight seal • Memory retaining polyurethane cover gasket • 300 series S.S hardware • Integral Mounting feet • Padlocking hasp • Molded-in back panel mounting inserts • Back panels available in standard AL and alternative SS,CS, FG • Dead front / swing panel configuration

New Datasheet Available For Easy Download:

Just Visit: www.stahlin.com

For additional information on Stahlin's Non-Metallic Enclosures products contact: Jolynn Stalsonburg, 500 Maple Street, Belding, Michigan 48809. Phone: 616-794-0700, fax: 616-794-3378. E-Mail: jstalsonburg@stahlin.com. Worldwide web: www.stahlin.com.

Receive up-to-date information by enrolling in our News Program:



[Have Questions? Request information online.](#)



Join Our RSS News Feed for up-to-date information

When you subscribe to a feed, it is added to the Common Feed List. Updated information from the feed is automatically downloaded to your computer and can be viewed in Internet Explorer and other programs.

[Visit Yahoo to learn more about RSS news feeds](#)

Click Here To: [Subscribe to OUR News feed](#)